







RoHS2.0&REACH Compliant

THE PART MEETS TECONN "GP001" COMPLIANCE NEW REV.



RECOMMENDED PCB LAYOUT(TOP VIEW)
THICKNESS 0.60MM;DEFAULT TOLERANCE:±0.05



PART NO.:

W 10 24 C3-A-XX-R

Pin NO.

Flow NO.

Plating:

01: Au G/F
05: Au 05u"
15: Au 15u"
30: Au 30u"

Packing:
R: Reel

USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A2	SSTXp1	B11	SSRXp1
A3	SSTXn1	B10	SSRXn1
A4	Vbus	B9	Vbus
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	Vbus	B4	Vbus
A10	SSRXn2	B3	SSTXn2
A11	SSRXp2	B2	SSTXp2
A12	GND	B1	GND

X. ± 0.35 .X ± 0.25 .XX ± 0.15 .XXX±	APPD: Henry Sun CHKD:	TITLE: USB TYPE C 母座板上双排SMT	TECONN
X* ± 2* .X* ± 1.5*	DR: Zhangjing	PART NO: W1024C3-A-XX-R	
UNITS: mm SCALE: 1:1	DWG NO: C-W1024C3-A-XX-R	CUSTOMER DRAWING	SHEET:1OF1 REV: C

C	TE2019-0027	Update Drawing	Drex	2019/04/23
B	TE2018-XXXX	Update Drawing	Zhangjing	2018/01/20
A	TE2016-XXXX	New Drawing	Cola Lee	2016/05/29
REV	ECN NO	DESCRIPTION	DESIGN	DATE